



Sheeps Foot Cutter Bar

BRIO-TECH PRESSURE CONTROLS

To cut wire from stuck toolstrings.
 The sheep's foot cutter bar is similar to that of a section of the stem without the threaded connections. On the upper end of the sheep's foot cutter bar is a fishing neck profile, with the bottom face being cut at an angle.
 A narrow slot is cut the length of the body, and a retaining bar the size of the slot is held in place with a series of spring pins through both the outer edge and bar.
 The thickness of the retainer bar is narrow to allow the line to move freely behind it.
 Sheep's foot cutters generally come in three and five foot lengths.
 The body O.D. measurements are affected by the tubing size, threaded guides may be utilized.

Applications:

Cutting wireline, slickline, or cable at the top of a rope sockets that may have become stuck in the wellbore.
 Cutting wireline, slickline, or cable from the top of Go-Devils in the wellbore.

Size	1.00"	1.25"	1.50"	1.75"	2.125"
Fishneck (")	1.00"	1.187"	1.375"	1.75"	1.75"
Fishneck (mm)	25.4mm	30.15mm	34.93mm	44.45mm	44.45mm
Over all Length (")	3.00' / 5.00'	3.00' / 5.00'	3.00' / 5.00'	3.00' / 5.00'	3.00' / 5.00'
Over all Length (mm)	1.5 / 0.9 m	1.5 / 0.9 m	1.5 / 0.9 m	1.5 / 0.9 m	1.5 / 0.9 m
Maximum OD (")	1.00"	1.25"	1.50"	1.75"	2.125"
Maximum OD (mm)	25.4mm	31.75mm	38.1mm	44.45mm	53.98mm
Maximum Line Size	0.108	0.150"	0.218"	0.250"	0.250"



Available with locator rings to centralize in the wellbore
 Contact your Brio-Tech representative for more information

BRIO-TECH PRESSURE CONTROLS - 3904 – 53RD AVENUE NW, EDMONTON, ALBERTA, CANADA T6B 3N7
 (780) 670-2020

PLEASE STATE PART DESCRIPTION AND SIZE WHEN ORDERING

