



Swaging Tool

Swaging tools are oblong shaped tools typically used to locate minor tight spots in the tubing string. Swaging tools typically come with upper and lower thread connections so that additional tools may be ran below if so desired.

Swaging tools also typically come with a through hole and bypass ports so that the tool may travel more freely in a wellbore full of fluid.

Applications:

Swaging tools may be used to locate undersized or tight spots in a tubing string that may adversely effect tools such as bottom hole plungers, bottom hole pumps, or anything that may require a specific minimum tubing diameter to function properly.

Swaging tools may be used in fishing operations involving slickline or wireline, these may locate the top of the wire or slickline and allow for more precise fishing operations.

Swaging tools may also be used for swaging out minor tight spaces such as collars, or very minor pipe imperfections.

BRIO-TECH PRESSURE CONTROLS

| Size | 1.660" | 1.900" | 2.375" | 2.875" | 3.50" |
|--------------------|-------------|-------------|-------------|-------------|-------------|
| Upper Thread Conn. | 0.938-10 UN | 0.938-10 UN | 0.938-10 UN | 0.938-10 UN | 1.062-10 UN |
| Fishneck (") | 1.187" | 1.187 | 1.375 | 1.75 | 1.75 |
| Fishneck (mm) | 30.14mm | 30.14mm | 34.93mm | 44.45mm | 44.45mm |
| Lower Thread Conn. | 0.938-10 UN | 0.938-10 UN | 0.938-10 UN | 0.938-10 UN | 1.062-10UN |
| Maximum OD (") | 1.51" | 1.657" | 1.906" | 2.347" | 2.867" |
| Maximum OD (mm) | 38.36mm | 42.08mm | 48.41mm | 59.61mm | 72.82mm |



*Alternate thread configurations, sizes, and lengths available upon request
Contact your Brio-Tech representative for more information

BRIO-TECH PRESSURE CONTROLS - 3904 – 53RD AVENUE NW, EDMONTON, ALBERTA, CANADA T6B 3N7
(780) 670-2020

PLEASE STATE PART DESCRIPTION AND SIZE WHEN ORDERING

