



Wax Cutter

The wax cutter is designed to cut paraffin wax from the ID of the wellbore on oil producing wells. The full 360 degree cutting surface of the wax cutter allows for a greater deal of paraffin removal per pass.

Applications:

The wax cutter is specifically designed to cut paraffin wax from the ID of tubing strings both while travelling into and out of the wellbore.

The wax cutter may also be used to clean hydrates from the wellbore before they can form a bridge in the tubing string.

Size	1.660"	1.900"	2.375"	2.875"	3.50"	4.50"
Upper Thread Conn.	0.938-10 UN	0.938-10 UN	0.938-10 UN	0.938-10 UN	1.062-10 UN	1.062-10 UN
Fishneck (")	1.187"	1.187"	1.375"	1.75"	1.75"	2.31"
Fishneck (mm)	30.14mm	30.14mm	34.93mm	44.45mm	44.45mm	58.67mm
Maximum OD (")	1.51"	1.657"	1.906"	2.347"	2.867"	3.965"
Maximum OD (mm)	38.36mm	42.08mm	48.41mm	59.61mm	72.82mm	100.71mm



*Alternate thread configurations, sizes, and lengths available upon request
Contact your Brio-Tech representative for more information

BRIO-TECH PRESSURE CONTROLS - 3904 – 53RD AVENUE NW, EDMONTON, ALBERTA, CANADA T6B 3N7
(780) 670-2020

PLEASE STATE PART DESCRIPTION AND SIZE WHEN ORDERING

