



Wire Brush - Extended

Wire brushes are used to clean the wellbore or related sub surface equipment of unwanted build up, scale ,or other debris that has formed in the wellbore.
The extended wire brush can be used to clean larger, r longer sections of the wellbore at once.

Applications:

Wire brushes can but used to clean the wellbore of sand or other debris that may be deposited over time from production, or introduced during the fracturing process.
Wire brushes can also be used to clean the seal bores of profile, or landing nipples prior the installation of blanking plugs, check valves, or other downhole equipment.
Wire brushed can also be used to clean the latching mechanisms in equipment such as sliding side doors, or locating latches of side pocket mandrels.

Size	2.375"	2.875"	3.50"	4.50"
Upper Thread Conn.	0.938-10 UN	0.938-10 UN	1.062-10 UN	1.062-10 UN
Fishneck (")	1.375	1.75	1.75"	2.31"
Fishneck (mm)	34.93mm	44.45mm	44.45mm	58.67mm
Length (")	38.00"	38.00"	38.00"	38.00"
Length (mm)	965.2mm	965.2mm	965.2mm	965.2mm



*Alternate thread configurations, sizes, and lengths available upon request
Contact your Brio-Tech representative for more information

BRIO-TECH PRESSURE CONTROLS - 3904 – 53RD AVENUE NW, EDMONTON, ALBERTA, CANADA T6B 3N7
(780) 670-2020

PLEASE STATE PART DESCRIPTION AND SIZE WHEN ORDERING

