




Wire / Center Spear

Used in conjunction with other wireline fishing tools to locate and retrieve lost or broken wireline. Wireline spears consists of two components, the locator sub, and the wireline spear. The body is a long rod shaped tool and pointed at the bottom. The locator sub has the ability to accept threaded rings depending on the ID of tubing worked with. Barbs attached to the body, point upward in a staggered pattern around the length of the body.

Applications:

To loosen compacted wireline nests in tubing.
Used in conjunction with wireline grabs when compacted nests are encountered.
May also be used to fish packer cups or rubber from wellbore.

Size	1.25"	1.50"	2.375"	2.875"	3.50"
Upper Thread	0.625 UNC	0.938-10 UN	0.938-10 UN	0.938-10 UN	1.062-10 UN
Fishneck (")	1.00"	1.00"	1.187"	1.375"	1.75"
Fishneck (mm)	25.4mm	25.4mm	30.15mm	34.93mm	44.45mm
Over all Length (")	24.00"	24.00"	24.00"	24.00"	24.00"
Over all Length (mm)	609.6mm	609.6mm	609.6mm	609.6mm	609.6mm
Maximum OD (")	1.31"	1.656"	1.906"	2.347"	2.867"
Maximum OD (mm)	33.27mm	42.06mm	48.41mm	48.41	72.82mm



*Alternate thread configurations and sizes available upon request
Contact your Brio-Tech representative for more information

BRIO-TECH PRESSURE CONTROLS - 3904 – 53RD AVENUE NW, EDMONTON, ALBERTA, CANADA T6B 3N7
(780) 670-2020

PLEASE STATE PART DESCRIPTION AND SIZE WHEN ORDERING

